


ZNTLS

Ledge Table – Straight

Ledge Table – Straight provides bar height narrow surface ideal for impromptu meeting areas and cafeterias. Ledge Tables can be specified as freestanding or built-up from start, middle and end components.

WHAT'S INCLUDED

Configurations	Included
Freestanding	1 F type Straight Worksurface 2 End Gable Assemblies 2 End Gable Top Plates
Start	1 S type Straight Worksurface 1 End and 1 Mid Gable Assemblies 1 End and 1 Mid Gable Top Plates
Middle	1 M type Straight Worksurfaces 1 Mid Gable Assembly 1 Mid type Gable Top Plate
End	1 E type Straight Worksurface 1 End Gable Assembly 1 End Gable Top Plate



All assemblies include one each upper and lower beam, two hooks, two cable manager kits and one cable manager extrusion when option “Y” is selected, mounting hardware.

NOTES

Foot rail and horizontal beam structures are finished in Greystone.

PRODUCT OPTIONS

Configuration	Height	Depth	Width	Worksurface Finish	Edge Trim Style	Wire Management	Legs Paint Finish
F Freestanding	42	18	48, 60, 72	Zones Worksurface Laminate	8 Flat (with Zone's Worksurface Laminate)	N No Y Yes	24 Greystone
S Start				Zones Seamless	H Full Knife (with Zone's Worksurface Laminate)		25 Crisp Grey
M Middle				Zones Veneer	5 Double Eased (with Zone's Seamless)		
E End					9 Flat (with Zone's Veneer) H Full Knife (with Zone's Veneer)		

SAMPLE ORDER CODE

ZNTLS F	42	18	48	2T	8	Y	24
---------	----	----	----	----	---	---	----

DIMENSIONS
INCHES / MM

H	D	W
42 / 1067	18 / 457	48 / 1219
42 / 1067	18 / 457	60 / 1524
42 / 1067	18 / 457	72 / 1829

PRICING

WORKSURFACE LAMINATE			SEAMLESS		VENEER	
Flat Edge	Full Knife Edge		Double Eased Edge	Flat Edge	Full Knife Edge	
FREESTANDING (F)						
784	825		832	1392	1417	
832	887		881	1410	1516	
865	922		923	1488	1602	
START (S)						
824	874		865	1323	1403	
880	950		925	1405	1496	
938	1024		986	1487	1588	
MIDDLE (M)						
524	566		573	1041	1109	
566	615		619	1119	1190	
604	662		663	1197	1269	
END (E)						
545	596		586	1044	1126	
602	671		648	1128	1217	
659	745		709	1210	1309	

If Wire Management is specified, add 38